

UCSF Chimera Quick Reference Guide

April 2013

Commands (*reverse function ~command available)

2dlabels	create labels with text, symbols, and arrows in 2D
ac	enable accelerators (keyboard shortcuts)
addaa	add an amino acid to a peptide N- or C-terminus
addcharge	assign partial charges to atoms
addh	add hydrogens
alias*	create an alias or list the existing aliases
align	align two atoms or sets of atoms along the line of sight
angle	measure angles formed by atoms or by axes and planes
aniso*	show thermal ellipsoids
aromatic*	show ring aromaticity
background	set background color, gradient, or image
bond*	add/delete bonds
bondzone*	make zoning tools use points along bonds
cd	change the working directory
center	center the view on specified atoms
changechains	reassign chain identifiers
chirality	report the R/S configuration of a chiral center
clip*	move global clipping planes
close	close a model
cofr*	report or change the center of rotation
color*	color atoms/bonds, ribbons, labels, surfaces
colordef	define a new color
combine	combine molecule models into a single model
coordset	play through frames of a trajectory
copy	save image files
coulombic	color molecular surfaces by Coulombic electrostatics
crystalcontacts	identify clashes between PDB symmetry copies
defattr	assign attribute values to atoms, residues, or models
define*	calculate and display axes, planes, centroids
delete	delete atoms and bonds
display*	display specified atoms
distance*	measure distances between atoms, axes, planes, centroids
echo	send text to the status line and Reply Log
export	save the scene (x3d, vrml, povray, renderman, stl, obj)
fillring*	show rings as filled
findclash*	identify clashes and contacts
findhbond*	(hbonds) identify hydrogen bonds
fitmap	fit atoms or map into map
fly	smoothly traverse a series of saved positions
focus*	adjust the view and center of rotation
freeze	stop all motion
getcrd	report coordinates
help	display the manual page for a command
hkage	create icosahedron as hexagon/pentagon mesh
intersurf	generate and display interface surfaces
invert	swap substituents of an atom
ksdssp	determine secondary structure from protein coordinates
label*	display atom labels
labelopt	control the information in atom labels

lighting	adjust lighting and shininess
linewidth	control the width of wire bonds
longbond*	show/hide pseudobonds representing missing segments
mask	extract volume data bounded by surfaces
match	perform least-squares fitting of specified atoms
matchmaker	(mmaker) align models in sequence, then in 3D
matrixcopy	apply the transformation of one model to another
matrixget	write the current transformation matrices to a file
matrixset	read and apply transformation matrices from a file
mclip*	control per-model clipping
mcopy	copy settings from one molecule model to another
measure	perform calculations on structures, surfaces, maps
meshmol	create a "molecule" to show surface mesh as sticks
minimize	energy-minimize structures
modelcolor	set color at the model level
modeldisplay*	set display at the model level
molmap	create a density map from atomic coordinates
morph	morph (interpolate) between different structures
move	translate models
movie	capture image frames and assemble them into a movie
msc*	color multiscale surfaces to match atoms
namesel*	save and name the current selection
nucleotides*	create special nucleotide representations
objdisplay*	display graphical objects
open*	read local files or fetch by ID
pause	pause script execution until the user presses a key
perframe*	specify commands to be executed at each display frame
play	script various complex motions
preset	apply a predefined combination of display settings
rainbow	color residues, chains, or models over a range
rangecolor	color over a range according to attribute values
read	execute a command file, updating display at the end
represent	control atom/bond style (wire, stick, bs, sphere)
reset	restore default or saved orientations
resrenumber	reassign residue numbers
ribbackbone*	allow display of both ribbon and backbone atoms
ribbon*	display ribbon
ribclass	set ribbon residue class
ribinsidecolor*	set a separate color for inside protein helix ribbons
ribrepr	control ribbon style (flat, edged, rounded)
ribscale	control ribbon scaling (Chimera default, licorice)
ribsspline	control ribbon path (B-spline or cardinal spline)
rlabel*	display residue labels
rmsd	evaluate the RMSD between specified sets of atoms
rock	rock (rotate back and forth)
roll	roll (rotate continuously)
rotation*	make a bond rotatable
runscript	run Python script with command-line arguments
save	save the current Chimera session
savepos*	save model positions
scale*	scale the view
scene*	save/restore scenes (positions, styles, colors, labels, etc.)
scolor	color surfaces by volume data or geometry
section	move global clipping planes in parallel
segment	act on segmentation models
select*	select atoms, (de)activate models for motion
set*	set visual effects, individual model rotation
setattr*	set an attribute to a specified value
shape	create a surface of a specified geometric shape
show*	display specified atoms, undisplay the others
sleep	pause script execution for a specified time
solvate	add solvent using AmberTools
sop	adjust capping, edit surface models
split	partition a molecule model into separate submodels
start	start Chimera tools by name
stereo*	switch amongst stereo options and mono viewing
stop	exit from Chimera
surface*	calculate and display molecular surfaces
surfcat	(msms cat) group atoms for surface calculations
surfrepr	(msms repr) control surface style (solid, mesh, dot)
swapaa	mutate amino acids or swap rotamers
swapna	mutate nucleic acid residues
sym*	generate symmetry-related copies of a structure
system	send a command to the system shell
thickness	move global clipping planes in opposite directions
tile*	arrange models in a plane
topography	plot values in a volume data plane as surface heights
transparency*	make atoms/bonds, ribbons, and surfaces transparent
turn	rotate models
vdw*	display van der Waals (VDW) dot surface
vdwdefine*	set VDW radii
vdwdensity	set VDW surface dot density
version	show copyright information and Chimera version
viewdock	start ViewDock and load docking results
volume	display volume data such as electron density
vop	edit volume data
vseries	display an ordered sequence of volume data sets
wait	suspend command processing until motion has stopped
window	adjust the view to contain the specified atoms
windoworigin	set graphics window location
windowsize*	adjust the dimensions of the graphics window
write	save atomic coordinates (pdb, mol2)
writesel	write a list of the currently selected (or unselected) items
zonesel	select atoms/surfs within cutoff of specified atoms/surfs

Miscellaneous Operations (Default Settings)

selection from screen	Ctrl-left mouse button
add/toggle selection	Shift-Ctrl-left mouse button
rotation	left mouse button
XY-translation	middle mouse button
scaling	right mouse button or Side View
preferences	Favorites... Preferences...
searching help	Help... Search Documentation...
reporting a problem	Help... Report a Bug...
mailing list	chimera-users@cgl.ucsf.edu

Specification Symbols			Specification Examples	
Symbol	Function	Usage	@/element=atno	atomic number
#	model number	# model (integer)	@/idatmType=type	Chimera atom type
#.	submodel number	#. submodel (integer)	@/label	whether the atom is labeled
:	residue	: residue (name or number)	@/label=label	text of the atom label
::	residue name	:: residue	@/labelColor=labcolor	color of the atom label
::	chain ID	:: chain	@/name=name	atom name
@	atom name	@atom	@/occupancy=occupancy	crystallographic occupancy
@.	alternate location ID	@. alt_loc	@/radius=radius	current VDW radius
-	range	specifies a range of models, submodels, or residues	@/serialNumber=n	serial number in the input file
,	name separator	separates models or residues, ranges of models or residues, or names of atoms	@/surfaceCategory=category	surface calculation category (main, ligand, etc.)
*	whole wildcard	matches whole atom or residue names, e.g., *@CA specifies the alpha carbons of all residues	@/surfaceDisplay	per-atom surface display bit (can be true for buried atoms without surface)
=	partial wildcard	matches partial atom or residue names, e.g., @C= specifies all atoms with names beginning with C	Selected Residue Attributes	
?	single-char wildcard	used for atom and residue names only, e.g., :G?? selects all residues with three-letter names beginning with G	Usage	Description
;	command separator	separates multiple commands on a single line	@/areaSAS=sasa	solvent-accessible surface area
z<	zone specifier	z<zone or zr<zone specifies all residues within zone angstroms, za<zone specifies all atoms (rather than entire residues) within that distance. Using > instead of < gives the complement.	@/areaSES=sesa	solvent-excluded surface area
&	intersection	intersection of specified sets	:isHet	residues in PDB HETATM records (or the mmCIF equivalent)
	union	union of specified sets	:isHelix	amino acid residues in helices
~	negation	negation of specified set	:isStrand or :isSheet	amino acid residues in strands
Selected Atom Attributes			@/kdHydrophobicity=value	Kyte-Doolittle amino acid hydrophobicity
Usage	Description		@/phi=angle	protein/peptide backbone phi angle
@/altLoc=altloc	alternate location ID		@/psi=angle	protein/peptide backbone psi angle
@/areaSAS=sasa	solvent-accessible surface area		@/ssId=N	secondary structure element identifier (1 for first helix and first strand, etc.)
@/areaSES=sesa	solvent-excluded surface area		@/uniprotIndex=N	residue number in corresponding UniProt sequence, if any
@/bfactor=bfactor	B-factor		Selected Molecule Model Attributes	
@/color=color	atom-level color assignment		Usage	Description
@/defaultRadius=rad	default VDW radius		#/ballScale=factor	ball radius relative to VDW radius
@/display	whether atom display bit is "on"		#/color=color	model-level color assignment
@/drawMode=mode	mode can be 0 (dot), 1 (sphere), 2 (endcap, as in stick), or 3 (ball)		#/display	model display bit
			#/lineWidth=width	linewidth of wire representation
			#/numAtoms=N	total number of atoms
			#/numResidues=M	total number of residues
			#/stickScale=factor	stick radius relative to bond radius
UCSF Chimera is developed by the Resource for Biocomputing, Visualization, and Informatics (RBVI) at the University of California, San Francisco, funded by the National Institutes of Health (NIGMS P41-GM103311). The software is copyrighted and licensed by the Regents of the University of California.				